NASA
National Aeronautics and
Space Administration

Lyndon B. Johnson Space Center
Houston, Texas 77058



SPACE SHUTTLE AEROTHERMODYNAMIC DATA REPORT



Data Management SERVICES

SPACE DIVISION CHRYSLER CORPORATION

May 1977

DMS-DR-2342
NASA CR-151,074

RESULTS OF PHASE CHANGE PAINT HEAT TRANSFER TEST UTILIZING 0.040 SCALE 50% FOREBODY MODELS (NO. 82-0) OF THE ROCKWELL INTERNATIONAL SPACE SHUTTLE ORBITER IN AEDC VKF HYPERSONIC TUNNEL B (TEST OH54B)

by

W. H. Dye
Shuttle Aerosciences
Rockwell International Space Division

Prepared under NASA Contract Number NAS9-13247

by

Data Management Services
Chrysler Corporation Michoud Defense-Space Division
New Orleans, La. 70189

for

Engineering Analysis Division

Johnson Space Center
National Aeronautics and Space Administration
Houston, Texas

WIND TUNNEL TEST SPECIFICS:

Test Number:	AEDC VKFB-V41B-82A
NASA Series Number:	OH54B
Model Number:	82-0
Test Dates:	July 21 through July 25, 1975
Occupancy Hours:	38

FACILITY COORDINATOR:

L. L. Trimmer
VKF-SH
ARO, Inc.
Arnold Air Force Station,
Tennessee 37389

Phone: (615) 455-2611, x7377

AEROTHERMODYNAMICS ANALYSIS ENGINEERS:

C. B. Blumer and L. Johnson
Mail Code AC78
Rockwell International
Space Division
12214 Lakewood Boulevard
Downey, California 90241

Phone: (213) 922-3669

PROJECT ENGINEERS:

W. H. Dye
Mail Code AD38
Rockwell International
Space Division
12214 Lakewood Boulevard
Downey, California 90241

Phone: (213) 922-5005

K. Hube and D. Carver
VKF-SH
ARO, Inc.
Arnold Air Force Station
Tennessee 37389

Phone: (615) 455-2611,
x360 or x7565

DATA MANAGEMENT SERVICES:

Prepared by: Liaison--D. A. Sarver
Operations--Maurice Moser, Jr.

Reviewed by: G. G. McDonald

Approved: J. L. Glynn, Manager
Data Operations

Concurrence: N. D. Kemp, Manager
Data Management Services

Chrysler Corporation Michoud Defense-Space Division assumes no responsibility for the data presented other than display characteristics.

RESULTS OF PHASE CHANGE PAINT HEAT TRANSFER TEST UTILIZING 0.040 SCALE 50% FOREBODY MODELS (NO. 82-0) OF THE ROCKWELL INTERNATIONAL SPACE SHUTTLE ORBITER IN AEDC VKF HYPERSONIC TUNNEL B (TEST OH54B)

by

W. H. Dye
Shuttle Aerosciences
Rockwell International Space Division

ABSTRACT

Results of aerodynamic heating phase change paint tests of the Rockwell International Space Shuttle Orbiter conducted in the AEDC VKF Tunnel B during July, 1975 are presented. The model was a 0.040 scale representation of the forward 50% of the orbiter. Surface roughness effects on boundary layer transition were investigated. The roughness was simulated by steel balls 0.020 and 0.025 inch in diameter and a 0.25 in. diameter hole simulating the forward ET attach socket. A nominal Mach number of 8 was tested with unit Reynolds number varying from 0.75×10^6/ft through 3.5×10^6/ft. Angle of attack was varied from 20° to 40°.

TABLE OF CONTENTS

INDEX OF MODEL FIGURES

INTRODUCTION

Aerodynamic heating phase change paint hypersonic wind tunnel tests were conducted on 0.040 scale 50% forebody models of the Rockwell International Space Shuttle Orbiter (models 82-0) to determine the effects of forward ET attach socket and roughness element size and location on boundary layer transition. The tests were conducted in the Arnold Engineering and Development Center VKF hypersonic wind tunnel B from July 21 to July 25, 1975. These tests, OH54B, were the second of three entries in the facility to complete OH54.

Two (2) different surface irregularities were tested:

1) small steel balls (boundary layer tripping device)

2) a .25 inch diameter hole located at X_o = 388 on the model (simulating ET attach socket)

The tests were conducted at Mach 8 and Reynolds numbers ranging between 0.75 x 10^6/ft and 3.5 x 10^6/ft. Model angle of attack was varied from 20° through 40°.

NOMENCLATURE

SYMBOL	MNEMONIC	DEFINITION
C_p	C	specific heat of the model material, BTU/lb-^oF
g		acceleration due to gravity. 32.17 ft/sec^2
h	H(TO)	heat transfer coefficient based on $T_{AW} = T_o$
h_s	HREF	reference heat-transfer coefficient based on Fay-Riddell theory, BTU/ft^2-sec.-^oR
ℓ	L	fuselage reference length. 1293.3 in.
M_∞	MACH	free stream Mach no.
N_r	R	reference nose radius (0.040 ft. model scale, 1 ft. full scale)
P_∞	P-INF	free stream static pressure, psia
P_r		Prandtl number
P_o	PO	tunnel stilling chamber pressure, psia
P_1, P_2		defined in context
q_∞	Q-INF	free-stream dynamic pressure, psia
R		universal gas constant, ft-lb$_f$/lb$_m$-^oR
Re/ft	RN/L	free stream unit Reynolds number, ft^{-1}
S_t	ST(TO)	Stanton number based on T_o:

$$ST(TO) = \frac{H(TO)}{\rho_\infty V_\infty \left[.2235 + 1.35\times10^{-4}(T_o + 560)\right] \times 32.17}$$

NOMENCLATURE (Continued)

SYMBOL	MNEMONIC	DEFINITION
	STREF	Reference Stanton number: $ST(TO) = \frac{HREF}{\rho_\infty V_\infty [.2235 + 1.35\times10^{-4}(T_o + 560)]\times 32.17}$
T_{aw}	TAW	Adiabatic wall temperature, ^oF
$\bar{T}$	TBAR	$\frac{T_{DC} - T_{IN}}{T_{aw} - T_{IN}}$
T_i	TI	temperature measured by thermocouple no. i, ^oF
T_{IN}	TIN	initial model temperature, ^oF
T_∞	T-INF	free stream static temperature-^oR
T_{pc}	TPC	paint melt temperature, ^oF
T_o	TO	tunnel stilling chamber temperature, ^oR
t	TIME	time from start of model injection, sec.
Δt	DEL TIME	time model exposed to airstream. sec.
V_e		velocity at edge of the boundary layer, ft/sec.
V_∞	V-INF	free stream velocity, ft/sec.
X		longitudinal coordinate
α	ALPHA	model angle of attack corrected for sting deflection, deg.
β	BETA	flow parameters defined in context; also sideslip angle, deg.
γ		ratio of specific heats of air
κ	K	model thermoconductivity, BTU/ft-sec-^oF
μ_∞	MU-INF	free stream viscosity, lb-sec/ft^2

NOMENCLATURE (Concluded)

SYMBOL	MNEMONIC	DEFINITION
μ_s		stagnation air viscosity, lb-sec/ft^2
μ_w		air viscosity along model wall, lb_m/ft-sec
ρ	RHO	model material density, lb_m/ft^3
ρ_w		air density along model wall, lb_m/ft^3
ρ_s		stagnation air density, lb_m/ft^3
ρ_∞	RHO-INF	free stream air density, slug/ft^3
ψ	YAW	model yaw angle, deg.
	BREF	wing span at reference span; m, ft.
	H/HREF	ratio of heat transfer coefficient based on $T_{aw}=T_o$ to reference heat transfer coefficient based on Fay-Riddell theory (100% recovery factor)
	LREF	reference length or wing mean aerodynamic chord; m, ft.
	SREF	wing area or reference area; m^2, ft^2
	XMRP YMRP ZMRP	moment reference point on X, Y, and Z axes
	X/L	longitudinal fuselage location, reference to nose; in tab. data, X/L is location of melt line on fuselage bottom centerline
	RUN NO.	denotes individual test run
	GROUP	same as Run No.
	FRAME	defined in test procedure section

CONFIGURATIONS INVESTIGATED

The models were 0.040 scale representations of the forward 50% of the Rockwell International Space Shuttle Orbiter. The models were contoured per Rockwell lines VL70-000140C.

Five (5) different models were utilized. They were designated as 82-1, 82-2, 82-10, 82-11 and 82-12. The -1 and -2 models were made of Grumman proprietary material 'G' cast on a steel sting. Models 82-10, -11 and -12 were cast from Lockheed proprietary material "LH" on a steel sting. Shrinkage during curing of the cast models reduced the scale of each model to 0.0397. Differences in the models were as follows:

Model No.	Test Configuration No.	Definition
82-1	1	Paint stripe model used as a reference for model coordinate system. Figure 2a defines its grid system.
82-2	2	Model with a 0.25 inch diameter hole located at x/ℓ = 0.0104 on the fuselage bottom centerline. The hole simulated the ET forward attach socket.
82-10	10	Model with a stainless steel insert located at x/ℓ = 0.0518 on the fuselage lower surface. Interchangeable trip rings, consisting of steel balls spot welded to a contoured fuselage segment, fit into the insert. Trip rings with 0.00 (no balls), 0.020, and 0.025 inch diameter balls were tested.
82-11	11	Model with stainless steel insert and trip rings (like No.10) located at x/ℓ = 0.11 on the fuselage lower surface. A trip ring with balls was tested.

CONFIGURATIONS INVESTIGATED (Continued)

Model No.	Test Configuration No.	Definition
82-12	12	Model with stainless steel insert and trip rings (like No.10) located at $x/\ell = 0.164$ on the fuselage lower surface. Trip rings with 0.00 (no balls), 0.020 and 0.025 inch diameter balls were tested.

The reference body length (ℓ) is 1293.3 inches.

TEST FACILITY DESCRIPTION

The Arnold Engineering Development Center (AEDC) is an Air Force Facility located in Tullahoma, Tennessee. The tunnel used, Tunnel B, is located in the von Karman Facility portion of this center. Engineering and other technical operations in this tunnel are performed by contractor personnel of ARO, Inc.

Tunnel B is a continuous, closed circuit, variable density wind tunnel with an axisymmetric contoured nozzle and a 50-inch diameter test section. The tunnel can be operated at a nominal Mach number of 6 or 8 at stagnation pressures from 20 to 300 and 50 to 900 psia, respectively, and at a stagnation temperature of up to 1350°R. The model may be injected into the tunnel for a test run and then retracted for model cooling or model changes without interrupting the tunnel flow.

TEST PROCEDURE

Tempilaq®, a fusible coating that changes phase from an opaque solid to a transparent liquid at temperatures specified by the manufacturer, was used to indicate the location of isotherms on the model surface. The paints used had melting temperatures of 169, 200, 250, 300, 350 and 400, degrees Fahrenheit.

A Beattie-Coleman Varitron® 70 mm sequence camera was used to record the progression of isotherms on the windward surface as a function of time during each test run. The camera was located on the top of the wind tunnel and photographed the bottom surface of the Orbiter models. The camera was operated at a nominal rate of 1 frame/sec. Kodak TRI-X Pan® black-and-white film was used.

Dual television monitors were used throughout the test to further record the effects of planform area reduction on heating rates and to facilitate on-line cross-referencing.

Prior to each test run, the model was cleaned with a solvent and spray-painted with the phase-change coating. Trip ring balls were protected using cardboard shields during cleaning and painting. Model temperature was measured using a thermocouple probe. The model was then injected into the wind tunnel for about 30 seconds, during which time the progression of the isotherms, indicated by the demarcation between melted and unmelted coating, was continuously photographed. The model was then retracted from the wind tunnel and the cycle repeated for the next run.

DATA REDUCTION

Thin film heat transfer coefficients were calculated for each melt line at which photographs were taken. The coefficients were calculated assuming three different recovery factors:

$$\frac{T_{aw}}{T_o} = 1.0$$

The following calculations were then performed to obtain thin film coefficients:

$$\bar{T} = \frac{T_{pc} - T_{IN}}{T_{aw} - T_{IN}}$$

$$T_{aw} = \left(\frac{T_{aw}}{T_o}\right) \times T_o$$

$$h = \frac{\beta \sqrt{k\rho C_p}}{\sqrt{t}}$$

where the flow parameter β results from iterative solution of:

$$1 - \bar{T} = e^{\beta^2} (1 - \text{erf } \beta)$$

Theoretical thin film heat transfer coefficients and stagnation point heating rates were calculated using the equations given below:

$$h_s = (.768)(C_p)(P_r^{-.6})(\rho_w \mu_w)^{.1}(\rho_s \mu_s)^{.4} \sqrt{\frac{dVe}{dx}}$$

where

$$P_r = \frac{\mu C_p}{k} \quad (\mu, C_p \text{ and } k \text{ for air})$$

$\frac{dVe}{dx}$ = The streamwise velocity gradient along the model surface

and

$$\frac{dVe}{dx} = \frac{1}{N_r}\sqrt{2\,Rg\,T_o\left(1 - \frac{1}{P_1P_2}\right)}$$

N_r = Nose radius, .040 foot radius (1 foot full scale)

$$P_1 = \left[\frac{\gamma + 1}{2} M_\infty^2\right]^{\frac{\gamma}{\gamma-1}}$$

$$P_2 = \left[\left(\frac{\gamma + 1}{2\gamma M_\infty^2 - (\gamma - 1)}\right)\right]^{\frac{\gamma}{\gamma-1}}$$

Locations of melt lines on the fuselage bottom centerline were manually measured using film. These locations were correlated with corresponding values of tunnel conditions and h/h_s calculated using the above equations. The result of this effort was a table giving h/h_s and frame number as a function of x/ℓ for each group number. These data were then arranged into datasets and input to the DATAMAN system. Resulting data are tabulated in the appendix. Data off the lower surface centerline were used for qualitative analysis but were not digitized. Photographs taken during the test showing all melt lines may be obtained by contacting the aerothermodynamics analysis engineers.

REMARKS

Results of OH54A indicated that nonuniform transition patterns were caused by nonuniform ball heights. Therefore, before OH54B commenced, considerable effort was expended to obtain accurate and precise measurements of the height of each steel ball after it was spot welded onto a trip ring.

The standard deviation of the ball heights for each ring was reduced to produce a more uniform transition pattern. The tolerance of the ball heights was reduced to $\pm$ 1.5% of the ball height to accomplish this. Any ball with measurements outside the allowable tolerance was removed, replaced, and remeasured until the tolerance limit was satisfied.

The measurements were made using an optical measuring microscope with special lighting and measurement techniques. Particular attention was given to determining the exact point of contact between the ball and the trip ring. Ball height measurements were obtained with a 10^{-5} inch precision and accurate to $\pm$ 10^{-4} inch.

RESULTS AND DISCUSSION

Uncertainties of the basic tunnel parameters were estimated from repeat calibrations of the PO and TO instruments and from the repeatability and uniformity of the tunnel flow during calibrations. The parameters PO, TO, and Mach No. with their uncertainties were then used to compute the uncertainties in the other parameters dependent on these by means of the Taylor series method of error propagation.

	Uncertainty, percent		
MACH NO.	PO	TO	RE/FT
± 0.3	± 0.5	± 0.5	± 1.2

An estimate of the data precision of phase change paint data is hampered by the fact that an observer must determine the location of the melt line. For this analysis, only uncertainties attributable to the measured parameters are considered. The parameters needed for the solution of the equation for the heat transfer coefficient, h, are T_{pc}, T_{IN}, T_{aw}, $\sqrt{\rho \kappa C_p}$, and Δt. The table below summarizes the nominal uncertainties in these specific parameters.

Parameter	Uncertainty (±)
Δt	± 1.0
$\sqrt{\rho \kappa C_p}$	± 10.0
T_{IN}	± 0.5
T_o (T_{aw})	± 1.0
T_{pc}	± 0.5

It should be remembered that the above uncertainties in T_{aw} and T_{pc} only reflect nominal measurement uncertainties. As previously mentioned, the interpretation of when phase change occurs (i.e., T_{pc}) is a matter of observer experience, and the "correct" assumption of what should be used for T_{aw} also requires engineering judgment. However, combining the above measurement uncertainties with the corresponding error sensitivity factor (derived by using the equation for the heat transfer coefficient, h, and taking the square root of the sum of the squares) yields the following:

for $T_{pc} \leq 200^{\circ}F$, h uncertainty $\approx \pm$ 13 percent

for $T_{pc} > 200^{\circ}F$, h uncertainty $\approx \pm$ 11 percent

REFERENCES

1) Hube, F. K., "NASA/RI OH54 Shuttle Transition Test Final Data," AEDC VKF Tunnel B Project V41B-82A, July 25, 1975.

2) Dye, W. H., "Pretest Information For Phase Change Paint Tests on .040 Scale 50% Forebody Models of the Rockwell International Space Shuttle Orbiter in the AEDC 'B' Hypersonic Wind Tunnel. OH54B," SD74-Sh-0254, Rockwell International, June, 1975.

TABLE I

TEST CONDITIONS

M_∞	P_o, psia	T_o, ^oR	h_s, $\frac{Btu}{ft^2\text{-}sec\text{-}^oR}$	Re/ft x 10^{-6}
7.93	155	1270	0.014	0.75
7.94	210	1275	0.016	1.00
7.95	265	1280	0.018	1.25
7.96	320	1290	0.020	1.50
7.97	342	1292	0.021	1.60
7.97	375	1295	0.022	1.75
7.98	425	1300	0.023	2.00
7.98	490	1310	0.025	2.25
7.99	555	1320	0.026	2.50
7.99	610	1325	0.027	2.75
7.99	641	1323	0.028	2.875
7.99	670	1330	0.029	3.00
8.00	735	1330	0.030	3.25
8.00	800	1335	0.031	3.50

TABLE II.

DATASET/RUN NUMBER COLLATION SUMMARY

DATASET IDENTIFIER NO.	CONFIGURATION	UNIT REYNOLDS NO. MILLION PER FOOT	TRIP		ANGLE OF ATTACK					
					20		30		40	
			x/ℓ	DIA	T_{pc}	GROUP	T_{pc}	GROUP	T_{pc}	GROUP
1*	-2, ET Attach Penetration	2.5	-	-					300	220
2	-10 Model	1.5	0.0518	0					200	212
3	with trip	2.0	↓	↓			200	213	250	214
4	at fwd.location	2.5					250	215	300	216
5	↓	1.0		0.020					200	186
6		1.5		↓			250	198		
7		1.5					250	199	250	187
8		1.75					250	197	300	196
9		2.0							300	188
10		2.0					300	195	300	189
11		2.25					300	191	300	190
12		2.5					350	192	400	193
13		2.75					400	194		
14		1.25		0.025			200	211	300	210
15		1.5		↓			250	199		
16		1.5					300	208	300	209
17		1.75					300	207	300	206
18		2.0					300	201	350	200
19		2.25					350	203	400	202
20	↓	2.5	↓	↓			350	205	400	204
21	-11, Model with	1.75	0.110	0.020			250	241	300	242
22	trip at	2.0	↓	↓			300	240	300	239
23	mid location	2.25					300	237	350	238
24	↓	2.5					350	236	350	235
25		2.75					350	233	400	234
26	↓	3.0	↓	↓			350	232		

* data unavailable.

TABLE II. - (Concluded)

DATASET/RUN NUMBER COLLATION SUMMARY

DATASET IDENTIFIER NO.	CONFIGURATION	UNIT REYNOLDS NO. MILLION PER FOOT	TRIP		ANGLE OF ATTACK					
					20		30		40	
			x/ℓ	DIA	T_{pc}	GROUP	T_{pc}	GROUP	T_{pc}	GROUP
27	-11 (Continued)	3.5	0.110	0.020			400	231		
28	-12, Model with	1.5	0.1684	0					200	181
29	trip at	2.0					200	182	250	183
30	aft location	2.5					250	184	300	185
31		1.25		0.020					250	141
32		1.5							250	138
33		1.5					200	139	250	140
34		1.75					200	143	300	142
35		2.0			200	137*	250	136	250	135
36		2.25			250	146*	300	145	350	144
37		2.5			250	147	350	148	400	149
38		2.75			250	150				
39		3.0			250	151	350	2	400	153
40		3.25			300	154				
41		3.5			300	155	300	156	400	157
42		0.75		0.025					169	180
43		1.0							200	179
44		1.25					250	178	250	177
45		1.5					250	176	250	175
46		1.6					250	174		
47		1.75			200	171*	250	172	300	173
48		2.0			200	168*	250	169	300	170
49		2.25			250	166	300	167		
50		2.5			250	163	350	164	400	165
51		2.75			250	162				
52		3.0			300	159	350	160	400	161
53		3.5			300	158				

TABLE III.

MODEL DIMENSIONAL DATA

MODEL COMPONENT: BODY - B_{60}

GENERAL DESCRIPTION: 50% Orbiter Forebody, Vehicle 140C.

NOTE: This body includes a small portion of the wing glove.

MODEL SCALE: 0.040

DRAWING NUMBER: VL70-000140C

DIMENSIONS:	FULL SCALE	MODEL SCALE
Length	645.15	25.80
Max Width	330.00	13.20

TABLE III (Continued)

MODEL DIMENSIONAL DATA

MODEL COMPONENT: CANOPY - C_{10}

GENERAL DESCRIPTION: Configuration 4 canopy and windshield as used with B_{25}, six glass panes in windshield

MODEL SCALE: 0.040

DRAWING NUMBER: VL70-000140B, 140C, 202B

DIMENSIONS:	FULL SCALE	MODEL SCALE
Length (X_o = 434.643 to 670) In.	235.357	9.414
Max Width		
Max Depth Glass - In.	28.00	1.12
Nose/windshield intersection, X_o =	434.643	17.386

Notes:

1. Positive directions of angles are indicated by arrows

2. For clarity, origins of wind and stability axes have been displaced from the center of gravity



Figure 1. - Axis System.



1 LOWER SURFACE ℄
2 M.H.B LINE
3 TANGENT LINE
4 45° TANGENT LINE
5 WATER PLANE 400
6 UPPER SURFACE ℄

a. Paint Stripe Model Grid Locations
Figure 2. - Model Sketches.



b. Model 82-10. -11, and -12 Trip Ring Insert

Figure 2. - Model Sketches.

a. Stainless Steel Insert

Figure 3. - Model Photographs.

b. Smooth Trip Ring
Figure 3. - Model Photographs.



c. Trip Ring with 0.020 Inch Diameter Balls
Figure 3. - Model Photographs.



d. Trip Ring with 0.025 Inch Diameter Balls
Figure 3. - Model Photographs.



e. Installed Smooth Trip Ring
Figure 3. - Model Photographs.



f. Grid Model
Figure 3. - Model Photographs.

g. Model Installation, Tunnel Open
Figure 3. - Model Photographs.

h. Model Installation, Tunnel Closed
Figure 3. - Model Photographs.

APPENDIX

TABULATED SOURCE DATA

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM002) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

RUN NO. 212/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.280	.10700	1.50000	200.00000	212.00000	3781.00000
40.000	.320	.11400	1.50000	200.00000	212.00000	3779.00000
40.000	.380	.12200	1.50000	200.00000	212.00000	3777.00000
40.000	.390	.13300	1.50000	200.00000	212.00000	3775.00000
40.000	.410	.14800	1.50000	200.00000	212.00000	3773.00000
40.000	.440	.16900	1.50000	200.00000	212.00000	3771.00000
40.000	.465	.20100	1.50000	200.00000	212.00000	3769.00000
40.000	.495	.22700	1.50000	200.00000	212.00000	3768.00000
	GRADIENT	.55780	.00000	.00342	.00000	-64.45079

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM003) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.000

RUN NO. 213/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.320	.07000	2.00000	200.00000	213.00000	3817.00000
30.000	.350	.07500	2.00000	200.00000	213.00000	3813.00000
30.000	.360	.07800	2.00000	200.00000	213.00000	3810.00000
30.000	.370	.08300	2.00000	200.00000	213.00000	3808.00000
30.000	.385	.08900	2.00000	200.00000	213.00000	3805.00000
30.000	.400	.09700	2.00000	200.00000	213.00000	3802.00000
30.000	.410	.10800	2.00000	200.00000	213.00000	3799.00000
30.000	.420	.11800	2.00000	200.00000	213.00000	3797.00000
30.000	.430	.13100	2.00000	200.00000	213.00000	3795.00000
30.000	.450	.14900	2.00000	200.00000	213.00000	3793.00000
30.000	.470	.17800	2.00000	200.00000	213.00000	3791.00000
	GRADIENT	.72316	.00000	-.00055	-.00055	-188.52057

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM003) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.000

RUN NO. 214/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.290	.12200	2.00000	250.00000	214.00000	3845.00000
40.000	.315	.13300	2.00000	250.00000	214.00000	3841.00000
40.000	.320	.14700	2.00000	250.00000	214.00000	3837.00000
40.000	.340	.16700	2.00000	250.00000	214.00000	3833.00000
40.000	.360	.18100	2.00000	250.00000	214.00000	3831.00000
40.000	.380	.19900	2.00000	250.00000	214.00000	3829.00000
40.000	.390	.22300	2.00000	250.00000	214.00000	3827.00000
40.000	.410	.25900	2.00000	250.00000	214.00000	3825.00000
40.000	.450	.32200	2.00000	250.00000	214.00000	3823.00000
	GRADIENT	1.24679	.00000	-.00033	.00000	-139.90600

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM004) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

RUN NO. 215/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.350	.11300	2.50000	250.00000	215.00000	3879.00000
30.000	.375	.12200	2.50000	250.00000	215.00000	3867.00000
30.000	.390	.14800	2.50000	250.00000	215.00000	3861.00000
30.000	.410	.19000	2.50000	250.00000	215.00000	3856.00000
30.000	.450	.24300	2.50000	250.00000	215.00000	3853.00000
30.000	.495	.27500	2.50000	250.00000	215.00000	3852.00000
	GRADIENT	1.28580	-.00001	.00000	.00000	-133.63597

DATE 22 APR 77 TABULATED DATA - OH54B

AEDC V41B-82A.OH54B.-10MODEL.TRIP FWD (RVM004) (05 MAR 77)

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

RUN NO. 216/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.280	.14000	2.50000	300.00000	216.00000	3904.00000
40.000	.290	.15100	2.50000	300.00000	216.00000	3900.00000
40.000	.300	.16500	2.50000	300.00000	216.00000	3896.00000
40.000	.315	.18400	2.50000	300.00000	216.00000	3892.00000
40.000	.335	.21900	2.50000	300.00000	216.00000	3887.00000
40.000	.350	.25500	2.50000	300.00000	216.00000	3884.00000
40.000	.375	.29000	2.50000	300.00000	216.00000	3882.00000
40.000	.405	.34700	2.50000	300.00000	216.00000	3880.00000
	GRADIENT	1.68062	.00000	.00000	.00000	-192.76764

AEDC V41B-82A.OH54B.-10MODEL.TRIP FWD (RVM005) (05 MAR 77)

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.000

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

RUN NO. 186/ 0 RN/L = 1.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.090	.17500	1.00000	200.00000	185.00000	2992.00000
40.000	.110	.15100	1.00000	200.00000	185.00000	2984.00000
40.000	.120	.14900	1.00000	200.00000	185.00000	2980.00000
40.000	.135	.14000	1.00000	200.00000	185.00000	2988.00000
40.000	.170	.12600	1.00000	200.00000	185.00000	2972.00000
40.000	.180	.12000	1.00000	200.00000	185.00000	2974.00000
40.000	.215	.11100	1.00000	200.00000	185.00000	2970.00000
40.000	.235	.10300	1.00000	200.00000	186.00000	2982.00000
	GRADIENT	-.47491	.00000	-.00010	.00010	135.25137

AEDC V41B-82A,0H54B,-10MODEL,TRIP FWD (RVM006) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

RUN NO. 198/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.025	.15800	1.50000	250.00000	198.00000	3311.00000
30.000	.095	.14500	1.50000	250.00000	198.00000	3315.00000
30.000	.110	.13400	1.50000	250.00000	198.00000	3319.00000
30.000	.120	.12600	1.50000	250.00000	198.00000	3323.00000
30.000	.130	.11900	1.50000	250.00000	198.00000	3327.00000
	GRADIENT	-.34677	-.00000	.00000	.00000	134.85230

AEDC V41B-82A,0H54B,-10MODEL,TRIP FWD (RVM007) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

RUN NO. 199/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.120	.13600	1.50000	250.00000	199.00000	3358.00000
30.000	.195	.14700	1.50000	250.00000	199.00000	3354.00000
30.000	.200	.16100	1.50000	250.00000	199.00000	3350.00000
30.000	.230	.18100	1.50000	250.00000	199.00000	3346.00000
30.000	.255	.20900	1.50000	250.00000	199.00000	3342.00000
30.000	.300	.25900	1.50000	250.00000	199.00000	3338.00000
	GRADIENT	.69099	.00000	.00000	-.00014	-118.82089

RUN NO. 187/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.315	.12700	1.50000	250.00000	187.00000	3019.00000
40.000	.350	.14600	1.50000	250.00000	187.00000	3009.00000
40.000	.375	.16000	1.50000	250.00000	187.00000	3005.00000
40.000	.390	.17300	1.50000	250.00000	187.00000	3001.00000
40.000	.410	.19200	1.50000	250.00000	187.00000	2999.00000
40.000	.440	.22700	1.50000	250.00000	187.00000	2995.00000
40.000	.465	.25500	1.50000	250.00000	187.00000	2993.00000
40.000	.480	.29600	1.50000	250.00000	187.00000	2991.00000
40.000	.495	.35700	1.50000	250.00000	187.00000	2989.00000
	GRADIENT	1.20027	.00000	.00045	-.00322	-153.74908

DATE 22 APR 77 TABULATED DATA - OH54B

AEDC V418-82A,OH54B,-10MODEL,TRIP FWD (RVM008) (05 MAR 77)

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.750

REFERENCE DATA

SREF =	1.0000 SQ.FT.	XMRP =	1.0000 IN.	XO
LREF =	1.0000 IN.	YMRP =	1.0000 IN.	YO
BREF =	1.0000 IN.	ZMRP =	1.0000 IN.	ZO
SCALE =	.0400			

RUN NO. 197/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.210	.13100	1.75000	250.00000	197.00000	3287.00000
30.000	.240	.15300	1.75000	250.00000	197.00000	3280.00000
30.000	.260	.19400	1.75000	250.00000	197.00000	3273.00000
30.000	.280	.21300	1.75000	250.00000	197.00000	3271.00000
30.000	.300	.23800	1.75000	250.00000	197.00000	3269.00000
30.000	.410	.27700	1.75000	250.00000	197.00000	3267.00000
	GRADIENT	.72845	-.00000	.00021	-.00011	-89.09109

RUN NO. 196/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.055	.19500	1.75000	300.00000	196.00000	3249.00000
40.000	.150	.21300	1.75000	300.00000	196.00000	3245.00000
40.000	.175	.24400	1.75000	300.00000	196.00000	3240.00000
40.000	.200	.29500	1.75000	300.00000	196.00000	3235.00000
40.000	.250	.32800	1.75000	300.00000	196.00000	3233.00000
40.000	.400	.34900	1.75000	300.00000	196.00000	3232.00000
	GRADIENT	.43822	-.00000	.00000	.00000	-52.38321

AEDC V418-82A,OH54B,-10MODEL,TRIP FWD (RVM009) (05 MAR 77)

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.000

REFERENCE DATA

SREF =	1.0000 SQ.FT.	XMRP =	1.0000 IN.	XO
LREF =	1.0000 IN.	YMRP =	1.0000 IN.	YO
BREF =	1.0000 IN.	ZMRP =	1.0000 IN.	ZO
SCALE =	.0400			

RUN NO. 188/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.060	.22500	2.00000	300.00000	188.00000	3039.00000
40.000	.090	.24100	2.00000	300.00000	188.00000	3036.00000
40.000	.125	.27200	2.00000	300.00000	188.00000	3033.00000
40.000	.185	.30200	2.00000	300.00000	188.00000	3031.00000
40.000	.390	.32100	2.00000	300.00000	188.00000	3030.00000
40.000	.495	.34400	2.00000	300.00000	188.00000	3029.00000
	GRADIENT	.24233	.00000	.00003	-.00002	-17.24128

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM010) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.000

RUN NO. 195/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.205	.18300	2.00000	300.00000	195.00000	3219.00000
30.000	.230	.22000	2.00000	300.00000	195.00000	3212.00000
30.000	.270	.25500	2.00000	300.00000	195.00000	3209.00000
30.000	.385	.28000	2.00000	300.00000	195.00000	3206.00000
	GRADIENT	.48147	.00000	.00000	.00000	-59.78877

RUN NO. 189/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.055	.20900	2.00000	300.00000	189.00000	3064.00000
40.000	.070	.22900	2.00000	300.00000	189.00000	3061.00000
40.000	.120	.25700	2.00000	300.00000	189.00000	3058.00000
40.000	.140	.29700	2.00000	300.00000	189.00000	3055.00000
40.000	.185	.31600	2.00000	300.00000	189.00000	3054.00000
40.000	.490	.33900	2.00000	300.00000	189.00000	3053.00000
	GRADIENT	.26007	.00000	.00000	.00000	-19.69245

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM011) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.250

RUN NO. 191/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.150	.15100	2.25000	300.00000	191.00000	3115.00000
30.000	.160	.16200	2.25000	300.00000	191.00000	3111.00000
30.000	.185	.18100	2.25000	300.00000	191.00000	3106.00000
30.000	.200	.21800	2.25000	300.00000	191.00000	3100.00000
30.000	.250	.24600	2.25000	300.00000	191.00000	3097.00000
30.000	.260	.25900	2.25000	300.00000	191.00000	3096.00000
30.000	.400	.27300	2.25000	300.00000	191.00000	3095.00000
	GRADIENT	.49559	.00000	.00000	.00000	-73.29164

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM011) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.250

RUN NO. 190/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.055	.23000	2.25000	300.00000	190.00000	3083.00000
40.000	.060	.29500	2.25000	300.00000	190.00000	3078.00000
40.000	.080	.31600	2.25000	300.00000	190.00000	3077.00000
40.000	.130	.34200	2.25000	300.00000	190.00000	3076.00000
	GRADIENT	1.12860	.00000	.00027	.00000	-64.65607

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM012) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

RUN NO. 192/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.060	.24300	2.50000	350.00000	192.00000	3138.00000
30.000	.065	.26600	2.50000	350.00000	192.00000	3135.00000
30.000	.110	.27600	2.50000	350.00000	192.00000	3134.00000
30.000	.440	.28700	2.50000	350.00000	192.00000	3133.00000
	GRADIENT	.07539	.00000	.00002	.00000	-8.13097

RUN NO. 193/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.055	.29200	2.50000	400.00000	193.00000	3165.00000
40.000	.060	.33500	2.50000	400.00000	193.00000	3160.00000
40.000	.120	.34600	2.50000	400.00000	193.00000	3159.00000
	GRADIENT	.55860	-.00000	.00049	.00000	-60.51421

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM013) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.750

RUN NO. 194/ 0 RN/L = 2.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.060	.26200	2.75000	400.00000	194.00000	3192.00000
30.000	.080	.31500	2.75000	400.00000	194.00000	3184.00000
30.000	.090	.31400	2.75000	400.00000	194.00000	3185.00000
30.000	.130	.28900	2.75000	400.00000	194.00000	3188.00000
30.000	.150	.28100	2.75000	400.00000	194.00000	3189.00000
30.000	.400	.27400	2.75000	400.00000	194.00000	3190.00000
	GRADIENT	-.05840	-.00000	.00000	-.00003	7.54845

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM014) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.250

RUN NO. 211/ 0 RN/L = 1.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.340	.08000	1.25000	200.00000	211.00000	3739.00000
30.000	.370	.08600	1.25000	200.00000	211.00000	3734.00000
30.000	.400	.09100	1.25000	200.00000	211.00000	3730.00000
30.000	.420	.10000	1.25000	200.00000	211.00000	3725.00000
30.000	.455	.10700	1.25000	200.00000	211.00000	3722.00000
30.000	.470	.11200	1.25000	200.00000	211.00000	3720.00000
	GRADIENT	.24877	-.00000	-.00083	-.00041	-146.77838

RUN NO. 210/ 0 RN/L = 1.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.455	.17700	1.25000	300.00000	210.00000	3698.00000
40.000	.460	.18100	1.25000	300.00000	210.00000	3696.00000
40.000	.470	.18500	1.25000	300.00000	210.00000	3694.00000
40.000	.475	.20200	1.25000	300.00000	210.00000	3688.00000
	GRADIENT	1.07999	.00000	.00000	.00000	-439.93398

AEDC V41B-82A,0H54B,-10MODEL,TRIP FWD (RVM015) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

RUN NO. 199/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.120	.13600	1.50000	250.00000	199.00000	3358.00000
30.000	.195	.14700	1.50000	250.00000	199.00000	3354.00000
30.000	.200	.16100	1.50000	250.00000	199.00000	3350.00000
30.000	.230	.18100	1.50000	250.00000	199.00000	3346.00000
30.000	.255	.20900	1.50000	250.00000	199.00000	3342.00000
30.000	.380	.25890	1.50000	250.00000	199.00000	3338.00000
	GRADIENT	.69899	.00000	.00000	-.00014	-118.82089

AEDC V41B-82A,0H54B,-10MODEL,TRIP FWD (RVM016) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

RUN NO. 288/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.270	.17800	1.50000	300.00000	208.00000	3619.00000
30.000	.300	.20500	1.50000	300.00000	208.00000	3611.00000
30.000	.320	.21300	1.50000	300.00000	208.00000	3609.00000
30.000	.340	.22300	1.50000	300.00000	208.00000	3607.00000
30.000	.390	.24200	1.50000	300.00000	208.00000	3604.00000
	GRADIENT	.51192	.00000	-.00075	-.00038	-117.00709

RUN NO. 209/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.250	.20300	1.50000	300.00000	209.00000	3651.00000
40.000	.290	.24900	1.50000	300.00000	209.00000	3642.00000
40.000	.330	.28300	1.50000	300.00000	209.00000	3638.00000
40.000	.390	.30700	1.50000	300.00000	209.00000	3636.00000
40.000	.400	.32100	1.50000	300.00000	209.00000	3635.00000
	GRADIENT	.72597	.00000	-.00037	.00000	-94.29929

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM017) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.750

RUN NO. 207/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.200	.17000	1.75000	300.00000	207.00000	3582.00000
30.000	.240	.19100	1.75000	300.00000	207.00000	3576.00000
30.000	.270	.21700	1.75000	300.00000	207.00000	3571.00000
30.000	.285	.23000	1.75000	300.00000	207.00000	3569.00000
30.000	.320	.24600	1.75000	300.00000	207.00000	3567.00000
	GRADIENT	.66401	-.00000	.00000	-.00037	-130.43827

RUN NO. 206/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.125	.32300	1.75000	300.00000	206.00000	3540.00000
	GRADIENT	.00090	.00000	.00000	.00000	.00000

AEDC V41B-82A,OH54B,-10MODEL,TRIP FWD (RVM018) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.000

RUN NO. 201/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.190	.18900	2.00000	300.00000	201.00000	3419.00000
30.000	.195	.22900	2.00000	300.00000	201.00000	3412.00000
30.000	.280	.24700	2.00000	300.00000	201.00000	3410.00000
30.000	.350	.25700	2.00000	300.00000	201.00000	3409.00000
	GRADIENT	.31039	.00000	.00000	.00000	-44.07114

RUN NO. 200/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.060	.28700	2.00000	350.00000	200.00000	3391.00000
40.000	.115	.30500	2.00000	350.00000	200.00000	3389.00000
40.000	.130	.32600	2.00000	350.00000	200.00000	3387.00000
40.000	.470	.33900	2.00000	350.00000	200.00000	3386.00000
	GRADIENT	.10014	.00000	.00000	.00000	-9.27340

DATE 22 APR 77 TABULATED DATA - 0H54B

AEDC V41B-82A,0H54B,-10MODEL,TRIP FWD (RVM019) (05 MAR 77)

REFERENCE DATA

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.250

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XQ
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

RUN NO. 203/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.270	.24900	2.25000	350.00000	203.00000	3474.00000
30.000	.390	.26300	2.25000	350.00000	203.00000	3472.00000
	GRADIENT	.11667	.00000	.00000	.00026	-16.66175

RUN NO. 202/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.060	.30500	2.25000	400.00000	202.00000	3446.00000
40.000	.120	.31200	2.25000	400.00000	202.00000	3445.00000
40.000	.400	.32700	2.25000	400.00000	202.00000	3443.00000
	GRADIENT	.06123	-.00000	.00000	.00000	-8.23998

AEDC V41B-82A,0H54B,-10MODEL,TRIP FWD (RVM020) (05 MAR 77)

REFERENCE DATA

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XQ
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

RUN NO. 205/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.320	.26100	2.50000	350.00000	205.00000	3518.00000
30.000	.370	.27000	2.50000	350.00000	205.00000	3517.00000
30.000	.450	.28000	2.50000	350.00000	205.00000	3516.00000
	GRADIENT	.14419	.00000	.00000	.00000	-15.11210

RUN NO. 204/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.080	.34100	2.50000	400.00000	204.00000	3494.00000
40.000	.120	.33000	2.50000	400.00000	204.00000	3495.00000
	GRADIENT	-.27500	.00000	.00119	.00000	24.99580

DATE 22 APR 77 TABULATED DATA - OH54B (RVM021) (05 MAR 77)

AEDC V41B-82A,OH54B,-11MODEL,TRIP MID

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.750

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

RUN NO. 241/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.210	.16100	1.75000	250.00000	241.00000	4546.00000
	GRADIENT	.00000	.00000	.00000	.00000	.00000

RUN NO. 242/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.000	.15500	1.75000	300.00000	242.00000	4601.00000
40.000	.220	.25300	1.75000	300.00000	242.00000	4578.00000
40.000	.250	.31700	1.75000	300.00000	242.00000	4573.00000
	GRADIENT	.57227	.00000	.00003	.00000	-109.21307

AEDC V41B-82A,OH54B,-11MODEL,TRIP MID (RVM022) (05 MAR 77)

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.000

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

RUN NO. 240/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.225	.14000	2.00000	300.00000	240.00000	4527.00000
30.000	.250	.16300	2.00000	300.00000	240.00000	4517.00000
30.000	.280	.22100	2.00000	300.00000	240.00000	4504.00000
30.000	.330	.28800	2.00000	300.00000	240.00000	4499.00000
	GRADIENT	1.26495	.00000	.00000	.00000	-267.01344

RUN NO. 239/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.140	.19100	2.00000	300.00000	239.00000	4483.00000
40.000	.150	.21100	2.00000	300.00000	239.00000	4479.00000
40.000	.170	.24000	2.00000	300.00000	239.00000	4475.00000
40.000	.190	.28500	2.00000	300.00000	239.00000	4471.00000
40.000	.200	.32100	2.00000	300.00000	239.00000	4469.00000
40.000	.270	.34400	2.00000	300.00000	239.00000	4468.00000
	GRADIENT	1.21189	.00000	.00000	.00023	-109.44639

AEDC V41B-82A,0H54B,-11MODEL,TRIP MID (RVM023) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.250

RUN NO. 237/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.190	.15500	2.25000	300.00000	237.00000	4428.00000
30.000	.200	.18500	2.25000	300.00000	237.00000	4420.00000
30.000	.220	.20900	2.25000	300.00000	237.00000	4416.00000
30.000	.240	.22500	2.25000	300.00000	237.00000	4414.00000
30.000	.260	.25800	2.25000	300.00000	237.00000	4411.00000
30.000	.320	.27200	2.25000	300.00000	237.00000	4410.00000
	GRADIENT	.86529	.00000	.00045	-.00023	-118.31975

RUN NO. 238/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.130	.24500	2.25000	350.00000	238.00000	4454.00000
40.000	.140	.31800	2.25000	350.00000	238.00000	4446.00000
40.000	.190	.34900	2.25000	350.00000	238.00000	4444.00000
	GRADIENT	1.37419	.00000	-.00062	.00000	-125.81113

AEDC V41B-82A,0H54B,-11MODEL,TRIP MID (RVM024) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

RUN NO. 236/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.200	.19400	2.50000	350.00000	236.00000	4373.00000
30.000	.250	.27100	2.50000	350.00000	236.00000	4360.00000
	GRADIENT	1.54000	.00000	.00000	.00000	-259.99761

RUN NO. 235/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.120	.26000	2.50000	350.00000	235.00000	4344.00000
40.000	.130	.36000	2.50000	350.00000	235.00000	4337.00000
	GRADIENT	10.00002	-.00015	.00000	.00000	-700.07442

AEDC V41B-82A,OH54B,-11MODEL,TRIP MID (RVM025) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.750

RUN NO. 233/ 0 RN/L = 2.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.170	.20400	2.75000	350.00000	233.00000	4302.00000
30.000	.190	.26700	2.75000	350.00000	233.00000	4293.00000
30.000	.420	.27800	2.75000	350.00000	233.00000	4292.00000
	GRADIENT	.19249	-.00000	-.00013	.00000	-25.13059

RUN NO. 234/ 0 RN/L = 2.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.125	.32800	2.75000	400.00000	234.00000	4322.00000
40.000	.185	.34000	2.75000	400.00000	234.00000	4321.00000
40.000	.450	.35300	2.75000	400.00000	234.00000	4320.00000
	GRADIENT	.06849	-.00000	-.00004	-.00004	-5.43313

AEDC V41B-82A,OH54B,-11MODEL,TRIP MID (RVM026) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 3.000

RUN NO. 232/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.330	.28600	3.00000	350.00000	232.00000	4270.00000
30.000	.430	.30200	3.00000	350.00000	232.00000	4269.00000
	GRADIENT	.16000	.00000	.00000	.00000	-9.99756

AEDC V41B-82A.OH54B.-11MODEL.TRIP MID (RVM027) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 3.500

RUN NO. 231/ 0 RN/L = 3.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.155	.30300	3.50000	400.00000	231.00000	4249.00000
30.000	.330	.28100	3.50000	400.00000	231.00000	4251.00000
30.000	.420	.29200	3.50000	400.00000	231.00000	4250.00000
	GRADIENT	-.05301	.00000	.00000	.00000	4.81783

AEDC V41B-82A.OH54B.-12MODEL.TRIP AFT (RVM028) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

RUN NO. 181/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.265	.08800	1.50000	200.00000	181.00000	2780.00000
40.000	.280	.09500	1.50000	200.00000	181.00000	2777.00000
40.000	.320	.10100	1.50000	200.00000	181.00000	2775.00000
40.000	.370	.10900	1.50000	200.00000	181.00000	2773.00000
40.000	.410	.12900	1.50000	200.00000	181.00000	2769.00000
40.000	.460	.14400	1.50000	200.00000	181.00000	2767.00000
40.000	.470	.15500	1.50000	200.00000	181.00000	2766.00000
40.000	.475	.16700	1.50000	200.00000	181.00000	2765.00000
40.000	.485	.18+00	1.50000	200.00000	181.00000	2764.00000
40.000	.495	.20700	1.50000	200.00000	181.00000	2763.00000
	GRADIENT	.42+45	.00000	.00000	-.00009	-66.80511

AEDC V41B-82A.0H54B,-12MODEL,TRIP AFT (RVM029) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.000

RUN NO. 182/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.320	.06000	2.00000	200.00000	182.00000	2820.00000
30.000	.335	.06200	2.00000	200.00000	182.00000	2818.00000
30.000	.355	.06500	2.00000	200.00000	182.00000	2814.00000
30.000	.365	.07000	2.00000	200.00000	182.00000	2811.00000
30.000	.385	.07500	2.00000	200.00000	182.00000	2808.00000
30.000	.400	.08100	2.00000	200.00000	182.00000	2805.00000
30.000	.410	.08800	2.00000	200.00000	182.00000	2802.00000
30.000	.415	.09400	2.00000	200.00000	182.00000	2800.00000
30.000	.430	.10200	2.00000	200.00000	182.00000	2798.00000
30.000	.450	.11200	2.00000	200.00000	182.00000	2795.00000
30.000	.465	.12500	2.00000	200.00000	182.00000	2794.00000
30.000	.475	.14600	2.00000	200.00000	182.00000	2792.00000
30.000	.495	.16000	2.00000	200.00000	182.00000	2790.00000
	GRADIENT	.61368	.00000	.00000	.00026	-179.62761

RUN NO. 183/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.270	.02500	2.00000	250.00000	183.00000	2855.00000
40.000	.285	.10000	2.00000	250.00000	183.00000	2852.00000
40.000	.300	.10600	2.00000	250.00000	183.00000	2849.00000
40.000	.320	.11200	2.00000	250.00000	183.00000	2846.00000
40.000	.330	.12100	2.00000	250.00000	183.00000	2843.00000
40.000	.370	.13500	2.00000	250.00000	183.00000	2839.00000
40.000	.390	.15600	2.00000	250.00000	183.00000	2835.00000
40.000	.400	.17200	2.00000	250.00000	183.00000	2833.00000
40.000	.420	.19300	2.00000	250.00000	183.00000	2831.00000
40.000	.450	.22400	2.00000	250.00000	183.00000	2829.00000
40.000	.470	.24600	2.00000	250.00000	183.00000	2828.00000
40.000	.495	.27700	2.00000	250.00000	183.00000	2827.00000
	GRADIENT	.79183	.00000	.00016	-.00016	-127.39113

AEDC V41B-82A,OH54B,-12MODEL,TRIP AFT (RVM030) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

RUN NO. 184/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.345	.08400	2.50000	250.00000	184.00000	2688.00000
30.000	.360	.09000	2.50000	250.00000	184.00000	2884.00000
30.000	.370	.09700	2.50000	250.00000	184.00000	2880.00000
30.000	.385	.10700	2.50000	250.00000	184.00000	2876.00000
30.000	.400	.11700	2.50000	250.00000	184.00000	2873.00000
30.000	.410	.13000	2.50000	250.00000	184.00000	2870.00000
30.000	.420	.14200	2.50000	250.00000	184.00000	2868.00000
30.000	.430	.15700	2.50000	250.00000	184.00000	2866.00000
30.000	.450	.17900	2.50000	250.00000	184.00000	2864.00000
30.000	.465	.21300	2.50000	250.00000	184.00000	2862.00000
30.000	.480	.24000	2.50000	250.00000	184.00000	2861.00000
	GRADIENT	1.14523	.00000	.00116	.00116	-202.90786

RUN NO. 185/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.285	.11900	2.50000	300.00000	185.00000	2923.00000
40.000	.290	.12700	2.50000	300.00000	185.00000	2919.00000
40.000	.300	.13800	2.50000	300.00000	185.00000	2915.00000
40.000	.315	.15600	2.50000	300.00000	185.00000	2910.00000
40.000	.330	.17700	2.50000	300.00000	185.00000	2906.00000
40.000	.340	.20100	2.50000	300.00000	185.00000	2903.00000
40.000	.370	.23600	2.50000	300.00000	185.00000	2900.00000
40.000	.385	.25300	2.50000	300.00000	185.00000	2899.00000
40.000	.395	.27400	2.50000	300.00000	185.00000	2898.00000
40.000	.420	.30100	2.50000	300.00000	185.00000	2897.00000
40.000	.465	.33300	2.50000	300.00000	185.00000	2896.00000
	GRADIENT	1.28+15	-.00000	-.00066	-.00016	-147.14263

DATE 22 APR 77 TABULATED DATA - OH54B (RVM031) (05 MAR 77)

AEDC V41B-82A.OH54B.-12MODEL.TRIP AFT

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.250

REFERENCE DATA

SREF	=	1.0000 SQ.FT.	XMRP	=	1.0000 IN. XO
LREF	=	1.0000 IN.	YMRP	=	1.0000 IN. YO
BREF	=	1.0000 IN.	ZMRP	=	1.0000 IN. ZO
SCALE	=	.0400			

RUN NO. 141/ 0 RN/L = 1.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.300	.12000	1.25000	250.00000	141.00000	1575.00000
40.000	.315	.12500	1.25000	250.00000	141.00000	1572.00000
40.000	.330	.13000	1.25000	250.00000	141.00000	1569.00000
40.000	.375	.14200	1.25000	250.00000	141.00000	1563.00000
40.000	.405	.15900	1.25000	250.00000	141.00000	1557.00000
40.000	.470	.17900	1.25000	250.00000	141.00000	1552.00000
40.000	.480	.19500	1.25000	250.00000	141.00000	1549.00000
	GRADIENT	.39041	-.00000	.00000	-.00027	-137.43950

(RVM032) (05 MAR 77)

AEDC V41B-82A.OH54B.-12MODEL.TRIP AFT

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

REFERENCE DATA

SREF	=	1.0000 SQ.FT.	XMRP	=	1.0000 IN. XO
LREF	=	1.0000 IN.	YMRP	=	1.0000 IN. YO
BREF	=	1.0000 IN.	ZMRP	=	1.0000 IN. ZO
SCALE	=	.0400			

RUN NO. 138/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.240	.14000	1.50000	250.00000	138.00000	1463.00000
40.000	.245	.14300	1.50000	250.00000	138.00000	1462.00000
40.000	.250	.15300	1.50000	250.00000	138.00000	1459.00000
40.000	.255	.16100	1.50000	250.00000	138.00000	1457.00000
40.000	.260	.17600	1.50000	250.00000	138.00000	1454.00000
40.000	.265	.18100	1.50000	250.00000	138.00000	1453.00000
40.000	.270	.19300	1.50000	250.00000	138.00000	1452.00000
40.000	.275	.20300	1.50000	250.00000	138.00000	1450.00000
40.000	.285	.21300	1.50000	250.00000	138.00000	1449.00000
40.000	.290	.22300	1.50000	250.00000	138.00000	1448.00000
40.000	.300	.23500	1.50000	250.00000	138.00000	1447.00000
40.000	.310	.25000	1.50000	250.00000	138.00000	1445.00000
40.000	.330	.26800	1.50000	250.00000	138.00000	1445.00000
40.000	.380	.29100	1.50000	250.00000	138.00000	1444.00000
	GRADIENT	1.18733	-.00000	-.00092	-.00023	-140.33761

AEDC V418-82A.0H54B.-12MODEL.TRIP AFT (RVM033) (05 MAR 77)

REFERENCE DATA

PARAMETRIC DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XQ
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

MACH = 8.000 RN/L = 1.500

RUN NO. 139/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.330	.07200	1.50000	200.00000	139.00000	1502.00000
30.000	.355	.07300	1.50000	200.00000	139.00000	1499.00000
30.000	.365	.07900	1.50000	200.00000	139.00000	1496.00000
30.000	.385	.08300	1.50000	200.00000	139.00000	1493.00000
30.000	.405	.09500	1.50000	200.00000	139.00000	1489.00000
30.000	.425	.09800	1.50000	200.00000	139.00000	1485.00000
30.000	.450	.10400	1.50000	200.00000	139.00000	1483.00000
30.000	.470	.11400	1.50000	200.00000	139.00000	1480.00000
30.000	.485	.12700	1.50000	200.00000	139.00000	1477.00000
	GRADIENT	.34592	.00000	-.00029	.00000	-161.79370

RUN NO. 140/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.250	.15600	1.50000	250.00000	140.00000	1525.00000
40.000	.265	.17500	1.50000	250.00000	140.00000	1521.00000
40.000	.275	.19500	1.50000	250.00000	140.00000	1518.00000
40.000	.290	.22200	1.50000	250.00000	140.00000	1515.00000
40.000	.315	.24900	1.50000	250.00000	140.00000	1513.00000
40.000	.330	.26700	1.50000	250.00000	140.00000	1512.00000
40.000	.360	.28900	1.50000	250.00000	140.00000	1511.00000
	GRADIENT	1.24609	-.00000	-.00095	-.00024	-122.89427

AEDC V41B-82A,OH54B,-12MODEL,TRIP AFT (RVM034) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.750

RUN NO. 143/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.255	.10300	1.75000	200.00000	143.00000	1618.00000
30.000	.265	.13300	1.75000	200.00000	143.00000	1612.00000
30.000	.280	.16400	1.75000	200.00000	143.00000	1609.00000
30.000	.305	.20300	1.75000	200.00000	143.00000	1607.00000
	GRADIENT	1.94978	.00001	.00000	.00134	-199.10894

RUN NO. 142/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.225	.20000	1.75000	300.00000	142.00000	1600.00000
40.000	.230	.21700	1.75000	300.00000	142.00000	1597.00000
40.000	.240	.23700	1.75000	300.00000	142.00000	1594.00000
40.000	.245	.25500	1.75000	300.00000	142.00000	1592.00000
40.000	.250	.27600	1.75000	300.00000	142.00000	1590.00000
40.000	.275	.30400	1.75000	300.00000	142.00000	1588.00000
40.000	.470	.32100	1.75000	300.00000	142.00000	1587.00000
	GRADIENT	.38421	.00000	-.00019	.00000	-35.89945

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM035) (05 MAR 77)

REFERENCE DATA

PARAMETRIC DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

MACH = 8.000 RN/L = 2.000

RUN NO. 136/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.225	.12700	2.00000	250.00000	136.00000	1370.00000
30.000	.230	.13700	2.00000	250.00000	136.00000	1367.00000
30.000	.235	.14000	2.00000	250.00000	136.00000	1366.00000
30.000	.240	.15300	2.00000	250.00000	136.00000	1363.00000
30.000	.245	.17000	2.00000	250.00000	136.00000	1360.00000
30.000	.255	.18500	2.00000	250.00000	136.00000	1358.00000
30.000	.260	.20500	2.00000	250.00000	136.00000	1356.00000
30.000	.270	.21700	2.00000	250.00000	136.00000	1355.00000
30.000	.275	.23300	2.00000	250.00000	136.00000	1354.00000
30.000	.285	.25200	2.00000	250.00000	136.00000	1353.00000
	GRADIENT	2.13666	.00000	.00000	-.00082	-285.45355

RUN NO. 135/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.230	.22000	2.00000	250.00000	135.00000	1343.00000
40.000	.235	.23500	2.00000	250.00000	135.00000	1341.00000
40.000	.240	.25400	2.00000	250.00000	135.00000	1339.00000
40.000	.250	.29500	2.00000	250.00000	135.00000	1335.00000
40.000	.260	.31300	2.00000	250.00000	135.00000	1335.00000
	GRADIENT	3.24826	.00000	-.00526	.00000	-270.72068

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM036) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.250

RUN NO. 145/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.220	.19400	2.25000	300.00000	145.00000	1662.00000
30.000	.230	.22200	2.25000	300.00000	145.00000	1658.00000
30.000	.240	.23100	2.25000	300.00000	145.00000	1657.00000
30.000	.275	.24200	2.25000	300.00000	145.00000	1656.00000
30.000	.465	.25400	2.25000	300.00000	145.00000	1655.00000
	GRADIENT	.16620	-.00000	-.00015	-.00007	-17.54867

RUN NO. 144/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.200	.26500	2.25000	350.00000	144.00000	1640.00000
40.000	.205	.30300	2.25000	350.00000	144.00000	1635.00000
40.000	.210	.33000	2.25000	350.00000	144.00000	1634.00000
40.000	.480	.34700	2.25000	350.00000	144.00000	1633.00000
	GRADIENT	.17691	.00000	.00007	.00003	-13.84960

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM037) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

RUN NO. 147/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.200	.09400	2.50000	250.00000	147.00000	1731.00000
20.000	.220	.11400	2.50000	250.00000	147.00000	1722.00000
20.000	.225	.13600	2.50000	250.00000	147.00000	1716.00000
20.000	.240	.16200	2.50000	250.00000	147.00000	1712.00000
20.000	.260	.18100	2.50000	250.00000	147.00000	1710.00000
	GRADIENT	1.53318	-.00002	.00000	.00000	-355.94848

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM037) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

RUN NO. 148/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.215	.20100	2.50000	350.00000	148.00000	1764.00000
30.000	.230	.23800	2.50000	350.00000	148.00000	1757.00000
30.000	.235	.25300	2.50000	350.00000	148.00000	1754.00000
30.000	.275	.27000	2.50000	350.00000	148.00000	1753.00000
30.000	.465	.28100	2.50000	350.00000	148.00000	1752.00000
	GRADIENT	.21699	.00000	-.00014	.00000	-28.07550

RUN NO. 149/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.190	.26900	2.50000	400.00000	149.00000	1789.00000
40.000	.200	.32200	2.50000	400.00000	149.00000	1782.00000
40.000	.260	.33300	2.50000	400.00000	149.00000	1781.00000
40.000	.470	.34500	2.50000	400.00000	149.00000	1780.00000
	GRADIENT	.17490	.00000	.00000	.00000	-19.41187

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM038) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.750

RUN NO. 150/ 0 RN/L = 2.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.260	.10500	2.75000	250.00000	150.00000	1853.00000
20.000	.265	.11700	2.75000	250.00000	150.00000	1849.00000
20.000	.275	.13400	2.75000	250.00000	150.00000	1845.00000
20.000	.290	.15400	2.75000	250.00000	150.00000	1842.00000
20.000	.300	.16200	2.75000	250.00000	150.00000	1841.00000
20.000	.470	.17200	2.75000	250.00000	150.00000	1840.00000
	GRADIENT	.23909	.00000	-.00016	-.00008	-40.18931

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM039) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 3.000

RUN NO. 151/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.235	.13100	3.00000	250.00000	151.00000	1881.00000
20.000	.245	.13900	3.00000	250.00000	151.00000	1878.00000
20.000	.325	.15900	3.00000	250.00000	151.00000	1873.00000
20.000	.355	.15400	3.00000	250.00000	151.00000	1874.00000
20.000	.425	.16900	3.00000	250.00000	151.00000	1871.00000
	GRADIENT	.18445	.00000	.00000	.00000	-47.60741

RUN NO. 152/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.195	.20700	3.00000	350.00000	152.00000	1902.00000
30.000	.205	.26500	3.00000	350.00000	152.00000	1895.00000
30.000	.450	.27800	3.00000	350.00000	152.00000	1894.00000
	GRADIENT	.17475	.00000	-.00006	.00000	-18.81726

RUN NO. 153/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.180	.27900	3.00000	400.00000	153.00000	1922.00000
40.000	.190	.34200	3.00000	400.00000	153.00000	1916.00000
40.000	.470	.35700	3.00000	400.00000	153.00000	1915.00000
	GRADIENT	.16882	.00000	-.00005	-.00005	-14.57562

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM040) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 3.250

RUN NO. 154/ 0 RN/L = 3.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.220	.14200	3.25000	300.00000	154.00000	1945.00000
20.000	.240	.17700	3.25000	300.00000	154.00000	1938.00000
	GRADIENT	1.75000	.00000	.00000	.00000	-349.99907

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM041) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 3.500

RUN NO. 155/ 0 RN/L = 3.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.210	.12900	3.50000	300.00000	155.00000	1988.00000
20.000	225	.15300	3.50000	300.00000	155.00000	1982.00000
	GRADIENT	1.59999	.00000	.00000	.00000	-399.98026

RUN NO. 156/ 0 RN/L = 3.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.185	.21500	3.50000	300.00000	156.00000	1985.00000
30.000	.190	.27900	3.50000	300.00000	156.00000	1979.00000
30.000	.400	.29500	3.50000	300.00000	156.00000	1978.00000
30.000	.480	.31700	3.50000	300.00000	156.00000	1977.00000
	GRADIENT	.23927	-.00000	.00000	-.00003	-17.78820

RUN NO. 157/ 0 RN/L = 3.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.175	.29000	3.50000	400.00000	157.00000	2001.00000
40.000	.190	.35400	3.50000	400.00000	157.00000	1996.00000
40.000	.470	.39500	3.50000	400.00000	157.00000	1995.00000
	GRADIENT	.21485	.00000	.00000	-.00002	-12.82825

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM042) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = .750

RUN NO. 180/ 0 RN/L = .75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.185	.09700	.75000	169.00000	180.00000	2741.00000
40.000	.210	.09100	.75000	169.00000	180.00000	2744.00000
40.000	.440	.08600	.75000	169.00000	180.00000	2747.00000
	GRADIENT	-.03463	.00000	-.00003	.00000	19.35826

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM043) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400.

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.000

RUN NO. 179/ 0 RN/L = 1.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.290	.11200	1.00000	200.00000	179.00000	2709.00000
40.000	.305	.12000	1.00000	200.00000	179.00000	2706.00000
40.000	.330	.12900	1.00000	200.00000	179.00000	2703.00000
40.000	.370	.14100	1.00000	200.00000	179.00000	2700.00000
40.000	.400	.15100	1.00000	200.00000	179.00000	2698.00000
40.000	.410	.16300	1.00000	200.00000	179.00000	2695.00000
40.000	.470	.17900	1.00000	200.00000	179.00000	2694.00000
40.000	.480	.20100	1.00000	200.00000	179.00000	2692.00000
	GRADIENT	.41845	.00000	.00000	.00000	-81.41465

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT (RVM044) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.250

RUN NO. 178/ 0 RN/L = 1.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.390	.12600	1.25000	250.00000	178.00000	2680.00000
30.000	.400	.13700	1.25000	250.00000	178.00000	2674.00000
30.000	.430	.15400	1.25000	250.00000	178.00000	2667.00000
30.000	.450	.16300	1.25000	250.00000	178.00000	2664.00000
30.000	.470	.18400	1.25000	250.00000	178.00000	2659.00000
	GRADIENT	.65920	-.00001	-.00272	-.00136	-243.74867

RUN NO. 177/ 0 RN/L = 1.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.230	.15300	1.25000	250.00000	177.00000	2624.00000
40.000	.240	.16300	1.25000	250.00000	177.00000	2621.00000
40.000	.250	.17800	1.25000	250.00000	177.00000	2617.00000
40.000	.260	.20000	1.25000	250.00000	177.00000	2613.00000
40.000	.275	.23100	1.25000	250.00000	177.00000	2609.00000
40.000	.305	.28400	1.25000	250.00000	177.00000	2605.00000
40.000	.470	.30500	1.25000	250.00000	177.00000	2604.00000
	GRADIENT	.60905	-.00000	-.00011	.00000	-59.96481

DATE 22 APR 77 TABULATED DATA - 0H54B

AEDC V41B-82A.0H54B.-12MODEL.TRIP AFT (RVM045) (05 MAR 77)

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.500

REFERENCE DATA

SREF	=	1.0000 SQ.FT.	XMRP	=	1.0000 IN. XO
LREF	=	1.0000 IN.	YMRP	=	1.0000 IN. YO
BREF	=	1.0000 IN.	ZMRP	=	1.0000 IN. ZO
SCALE	=	.0400			

RUN NO. 176/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.240	.12500	1.50000	250.00000	176.00000	2594.00000
30.000	.255	.14400	1.50000	250.00000	176.00000	2586.00000
30.000	.270	.17000	1.50000	250.00000	176.00000	2579.00000
30.000	.280	.19300	1.50000	250.00000	176.00000	2575.00000
30.000	.300	.21900	1.50000	250.00000	176.00000	2572.00000
30.000	.315	.23000	1.50000	250.00000	176.00000	2571.00000
30.000	.400	.24200	1.50000	250.00000	176.00000	2570.00000
30.000	.475	.25800	1.50000	250.00000	176.00000	2569.00000
	GRADIENT	.50950	-.00000	.00017	-.00008	-79.89713

RUN NO. 175/ 0 RN/L = 1.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.200	.17000	1.50000	250.00000	175.00000	2558.00000
40.000	.215	.20900	1.50000	250.00000	175.00000	2552.00000
40.000	.225	.25700	1.50000	250.00000	175.00000	2548.00000
40.000	.240	.32900	1.50000	250.00000	175.00000	2545.00000
40.000	.265	.53400	1.50000	250.00000	175.00000	2542.00000
	GRADIENT	5.64695	.00000	.00000	.00062	-240.89815

DATE 22 APR 77 TABULATED DATA - 0H54B (RVM046) (05 MAR 77)

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.600

REFERENCE DATA

SREF	=	1.0000 SQ.FT.	XMRP	=	1.0000 IN. XO
LREF	=	1.0000 IN.	YMRP	=	1.0000 IN. YO
BREF	=	1.0000 IN.	ZMRP	=	1.0000 IN. ZO
SCALE	=	.0400			

RUN NO. 174/ 0 RN/L = 1.60 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.230	.12300	1.60000	250.00000	174.00000	2553.00000
30.000	.245	.14200	1.60000	250.00000	174.00000	2525.00000
30.000	.250	.16000	1.60000	250.00000	174.00000	2520.00000
30.000	.265	.18700	1.60000	250.00000	174.00000	2515.00000
30.000	.305	.23500	1.60000	250.00000	174.00000	2510.00000
30.000	.460	.24900	1.60000	250.00000	174.00000	2509.00000
	GRADIENT	.49462	.00000	.00000	.00000	-77.95958

(RVM047) (05 MAR 77)

AEDC V41B-82A,0H54B,-12MODEL,TRIP AFT

PARAMETRIC DATA

MACH = 8.000 RN/L = 1.750

REFERENCE DATA

SREF	=	1.0000 SQ.FT.	XMRP	=	1.0000 IN. XO
LREF	=	1.0000 IN.	YMRP	=	1.0000 IN. YO
BREF	=	1.0000 IN.	ZMRP	=	1.0000 IN. ZO
SCALE	=	.0400			

RUN NO. 172/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.230	.12500	1.75000	250.00000	172.00000	2469.00000
30.000	.255	.19200	1.75000	250.00000	172.00000	2453.00000
30.000	.275	.22300	1.75000	250.00000	172.00000	2450.00000
30.000	.300	.23600	1.75000	250.00000	172.00000	2449.00000
30.000	.490	.25300	1.75000	250.00000	172.00000	2448.00000
	GRADIENT	.34334	-.00000	-.00007	.00000	-47.16129

RUN NO. 173/ 0 RN/L = 1.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.200	.18700	1.75000	300.00000	173.00000	2498.00000
40.000	.225	.30500	1.75000	300.00000	173.00000	2492.00000
40.000	.470	.32100	1.75000	300.00000	173.00000	2481.00000
	GRADIENT	.32235	-.00000	-.00006	-.00006	-39.19915

AEDC V418-82A,0H54B,-12MODEL,TRIP AFT (RVM048) (05 MAR 77)

REFERENCE DATA

PARAMETRIC DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

MACH = 8.000 RN/L = 2.000

RUN NO. 169/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.215	.12700	2.00000	250.00000	169.00000	2378.00000
30.000	.230	.16500	2.00000	250.00000	169.00000	2369.00000
30.000	.240	.18800	2.00000	250.00000	169.00000	2366.00000
30.000	.260	.22200	2.00000	250.00000	169.00000	2363.00000
	GRADIENT	2.10292	.00000	.00000	.00000	-322.80691

RUN NO. 170/ 0 RN/L = 2.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.190	.20701	2.00000	300.00000	170.00000	2399.00000
40.000	.205	.3130	2.00000	300.00000	170.00000	2389.00000
40.000	.480	.33501	2.00000	300.00000	170.00000	2388.00000
	GRADIENT	.27984	.00000	-.00010	-.00005	-22.60113

AEDC V418-82A,0H54B,-12MODEL,TRIP AFT (RVM049) (05 MAR 77)

REFERENCE DATA

PARAMETRIC DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

MACH = 8.000 RN/L = 2.250

RUN NO. 166/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.260	.11500	2.25000	250.00000	166.00000	2277.00000
20.000	.290	.16300	2.25000	250.00000	166.00000	2265.00000
	GRADIENT	1.53999	.00003	.00000	.00000	-400.01583

RUN NO. 167/ 0 RN/L = 2.25 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.215	.19000	2.25000	300.00000	167.00000	2298.00000
30.000	.225	.24300	2.25000	300.00000	167.00000	2291.00000
30.000	.470	.25600	2.25000	300.00000	167.00000	2290.00000
	GRADIENT	.16416	-.00000	-.00006	.00000	-18.81775

AEDC V41B-82A,OH54B,-12MODEL,TRIP AFT (RVM050) ; 05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.500

RUN NO. 163/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.235	.12300	2.50000	250.00000	163.00000	2138.00000
20.000	.255	.15900	2.50000	250.00000	163.00000	2131.00000
20.000	.280	.17500	2.50000	250.00000	163.00000	2129.00000
	GRADIENT	1.13443	.00002	.00000	.00000	-195.11289

RUN NO. 164/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.200	.23100	2.50000	350.00000	164.00000	2161.00000
30.000	.205	.26700	2.50000	350.00000	164.00000	2156.00000
30.000	.470	.28700	2.50000	350.00000	164.00000	2154.00000
	GRADIENT	1.14391	-.00000	.00000	-.00003	-17.08004

RUN NO. 165/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.180	.27300	2.50000	400.00000	165.00000	2250.00000
40.000	.185	.31600	2.50000	400.00000	165.00000	2244.00000
40.000	.200	.32500	2.50000	400.00000	165.00000	2243.00000
40.000	.460	.33500	2.50000	400.00000	165.00000	2242.00000
40.000	.490	.34700	2.50000	400.00000	165.00000	2241.00000
	GRADIENT	.13237	.00000	-.00006	-.00003	-15.21010

AEDC V41B-82A.0H54B.-12MODEL.TRIP AFT (RVM051) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 2.750

RUN NO. 162/ 0 RN/L = 2.75 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.220	.11500	2.75000	250.00000	162.00000	2117.00000
20.000	.230	.13600	2.75000	250.00000	162.00000	2112.00000
20.000	.240	.15500	2.75000	250.00000	162.00000	2109.00000
20.000	.265	.17400	2.75000	250.00000	162.00000	2107.00000
	GRADIENT	1.26480	.00000	.00170	-.00170	-204.47778

AEDC V41B-82A.0H54B.-12MODEL.TRIP AFT (RVM052) (05 MAR 77)

REFERENCE DATA

SREF = 1.0000 SQ.FT. XMRP = 1.0000 IN. XO
LREF = 1.0000 IN. YMRP = 1.0000 IN. YO
BREF = 1.0000 IN. ZMRP = 1.0000 IN. ZO
SCALE = .0400

PARAMETRIC DATA

MACH = 8.000 RN/L = 3.000

RUN NO. 159/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.225	.12700	3.00000	300.00000	159.00000	2054.00000
20.000	.250	.16900	3.00000	300.00000	159.00000	2042.00000
20.000	.480	.18000	3.00000	300.00000	159.00000	2040.00000
	GRADIENT	.14420	.00000	-.00006	.00000	-36.52482

RUN NO. 160/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
30.000	.190	.20900	3.00000	350.00000	160.00000	2076.00000
30.000	.195	.27600	3.00000	350.00000	160.00000	2068.00000
30.000	.400	.28900	3.00000	350.00000	160.00000	2067.00000
30.000	.470	.30600	3.00000	350.00000	160.00000	2066.00000
	GRADIENT	.23013	-.00000	-.00006	.00000	-22.66675

RUN NO. 161/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
40.000	.175	.28700	3.00000	400.00000	161.00000	2096.00000
40.000	.180	.34300	3.00000	400.00000	161.00000	2091.00000
40.000	.270	.35800	3.00000	400.00000	161.00000	2090.00000
40.000	.490	.37600	3.00000	400.00000	161.00000	2089.00000
	GRADIENT	.19395	.00000	-.00005	.00000	-14.29795

AEDC V418-82A,OH54B,-12MODEL,TRIP AFT (RVM053) (05 MAR 77)

REFERENCE DATA

SREF	=	1.0000 SQ.FT.	XMRP	=	1.0000 IN. XO
LREF	=	1.0000 IN.	YMRP	=	1.0000 IN. YO
BREF	=	1.0000 IN.	ZMRP	=	1.0000 IN. ZO
SCALE	=	.0400			

PARAMETRIC DATA

MACH = 8.000 RN/L = 3.500

RUN NO. 158/ 0 RN/L = 3.50 GRADIENT INTERVAL = -5.00/ 5.00

ALPHA	X/L	H/HREF	RN/L	TPC	GROUP	FRAME
20.000	.200	.13600	3.50000	300.00000	158.00000	2024.00000
20.000	.225	.17600	3.50000	300.00000	158.00000	2016.00000
20.000	.480	.19300	3.50000	300.00000	158.00000	2014.00000
	GRADIENT	.14783	.00000	-.00005	.00000	-24.35661